

Web Languages and Technologies

Faculdade de Engenharia da Universidade do Porto
26th January 2017

Duration: 2h / No Consultation

Name: _____

Number: _____

Note: In multiple choice questions, you lose $\frac{1}{3}$ of the grade for each wrong answer but you can select more than one option.

- 1 val. 1. In order for two *inputs* with type *radio* to be considered in the same group, they must...
- Be in consecutive lines.
 - Have the same *value* attribute.
 - Have the same *name* attribute.
 - Have the same *group* attribute.
- 1 val. 2. What CSS selector should we use to select the title of the first article having class *featured*?
- `article.featured :first-child h2 { ... }`.
 - `article.featured h2:first-child { ... }`.
 - `article:first-child .featured h2 { ... }`.
 - `article.featured:first-child h2 { ... }`.
- 1 val. 3. A *Session Hijacking* attack is done by...
- Changing a session cookie using CSRF.
 - Obtaining a session cookie that was sent insecurely.
 - Forcing a user to use a certain session cookie.
 - Taking advantage of cookies stored in the browser in clear text.
- 1 val. 4. Is a password, that was hashed with a strong cryptographic hashing algorithm but without using a *salt*, virtually impossible to reverse?
- It is never possible to reverse.
 - It is always easy to reverse.
 - It is possible to reverse if we know what algorithm was used.
 - Only if the password is large and complex.
- 1 val. 5. When browsing a web site whose URL starts with *https://* we can always be sure...
- The communication is encrypted.
 - A *Man in the Middle* attack is not possible.
 - The server is using version 2 of the HTTP protocol.
 - The HTML version is 4 or above.

(continues on the other side...)

1 val.

6. In PHP, the `strpos` function returns the position, starting in 0, of the first occurrence of a *string* inside another *string*; or *false* if the *string* is not found. After the following code, which is the correct way to test if the *string* has not been found?

```
$pos = strpos($search, $test);
```

- if (!\$pos) echo "Not found";
- if (\$pos != true) echo "Not found";
- if (\$pos === false) echo "Not found";
- if (\$pos == false) echo "Not found";

1 val.

7. In Javascript, a function is...

- A prototype.
- An object.
- A class.
- A context.

1 val.

8. In XPath, what is the default axis?

- element
- parent
- comment
- child